

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027184 A1

(51) International Patent Classification⁷: **E04H 6/28**

(21) International Application Number:
PCT/NL2003/000649

(22) International Filing Date:
19 September 2003 (19.09.2003)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1021501 20 September 2002 (20.09.2002) NL

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: VAN CROONENBORGH, Johan [NL/NL];
Oostmaaslaan 672, NL-3063 DJ Rotterdam (NL).


Published:

— with international search report

(74) Agents: DOHMEN, Johannes, Maria, Gerardus et al.; Algemeen Octrooi-en Merkenbureau, P.O. Box 645, NL-5600 AP Eindhoven (NL).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR STORING VEHICLES



(57) Abstract: The invention provides a device for storing vehicles, which device comprises a plurality of storage locations for said vehicles lying beside and above each other, at least one exchange location connecting to the surroundings of the device, wherein all the aforesaid locations comprise an open supporting platform for supporting a vehicle. The device furthermore comprises means of transport for transporting a vehicle between said at least one exchange location and a storage location, said means of transport comprising a horizontally movable guide system for guiding a lift in vertical direction, which lift comprises a lift platform which can move in horizontal direction between said lift and said locations and which can pass an open supporting platform in vertical direction for transferring a vehicle between the supporting platform in question and the lift platform. The exchange location further comprises a fill-up platform which, in a closed position thereof, in which it is aligned with the open supporting platform of the exchange location, forms a substantially closed surface, wherein the fill-up platform can be moved in downward direction from the closed position in order to create space for the lift platform to pass the supporting platform of said at least one exchange location in vertical direction.

WO 2004/027184 A1